



備考) 左図の吊上げ反転インサートには、内・外吊上げ兼用ダブルハンガーを用いています。(樹脂製インサート) また、吊上げには専用吊り金具を使用し、製品面に密着するまで締め込んで下さい。

単位：mmあるいは本あるいはkg

種類	国交省記号	呼び	寸法														配筋						参考質量 (kg)									
																	横鉄筋				縦鉄筋											
			外側鉄筋		底版内側鉄筋		径	数量 (本)	径	数量 (本)																						
			径又は呼び	数量(L=2000)	数量(L=1000)	径又は呼び					数量(L=2000)	数量(L=1000)																				
1種 歩道用	PU2	250	250	230	250	40	55	55	55	20	90	120	50	2000 又は 1000	450	395	4.00	10	6	—	4.00	11	290	145								
		300A	300	280	300			60	60			95			500	455												13	348	174		
		300B		270	400			65	65							560	5.00								15	497	248					
		300C		260	500			70	70						665											14	457	228				
		400A	400	370	400			65	65			110	135		600	575										16	536	268				
		400B		360	500			70	70							680											17	594	297			
		500A	500	460			45	60				125	150		720	695												21	680	340		
		500B		450	600			75	75							800	D6															
3種 車道用	PU3	250	250	230	250	45	55	65	65	30	90	120	50	2000 又は 1000	460	405	D6	14	7	—	4.00	11	335	167								
		300A	300	280	300	50		70	70			95	140		520	465														15	477	238
		300B		270	400			80	80							565	D6	10	6									17	580	290		
		300C		260	500			80	80						675																19	640
		400A	400	370	400	55		70	70			110			630	580														20	706	353
		400B		360	500			80	80							690																
		500A	500	460			60	60				125	155		750	690																
		500B		450	600			90	90							815																

JIS A 5372 附属書E
路面排水側溝類 推奨仕様E-3
縦断面用 (通称：JIS側溝)

落ちふた式U形側溝(本体) 製品図

Sheet Size
A4

Scale
1:12.000

株式会社 サイコン